

Electronic Universal Testing Model -UTE - HGFL -100 T



Universal Testing Machine UTE100I-6 Pillar . Servo Universal Testing Machine UTE-100T

Features :

- Hydraulic front loading wedge action grips
- Loading Accuracy as high + 1%
- Straining at variable speeds to suit a wide range of materials.
- Printer & PC Graphs enables to study the behavior of the material
- Continuous roll autographic recorder supplied as standard to enable study of the behavior of materials
- Motor driven threaded columns for quick effortless adjustment of lower cross-head-to facilitate rapid fixing of test specimen.
- High reading accuracy due to large size and design of dial.
- Wide range of standard and special accessories, including load stabilizer.
- Easy loading of specimens.
- Large effective clearance between columns enables testing of standards specimens as well as structures.
- Simple controls for easy of operation.
- Robust staining frame of an extremely rigid construction.

Features :

- Hydraulic front loading wedge action grips
- Loading Accuracy as high + 1%
- Straining at variable speeds to suit a wide range of materials.
- Printer & PC Graphs enables to study the behavior of the material
- Continuous roll autographic recorder supplied as standard to enable study of the behavior of materials
- Motor driven threaded columns for quick effortless adjustment of lower cross-head-to facilitate rapid fixing of test specimen.
- High reading accuracy due to large size and design of dial.
- Wide range of standard and special accessories, including load stabilizer.
- Easy loading of specimens.
- Large effective clearance between columns enables testing of standards specimens as well as structures.
- Simple controls for easy of operation.
- Robust staining frame of an extremely rigid construction.

- Safe operation ensured be means of safety devices.
- Fully enclosed and protected pressure transducer
- RS 232 serial port to transfer data to computer for analysis/storage, evaluation etc.
- Manual control & release valve operation

Application :

VEW Electronic Universal Testing Machine is designed for testing metals and other materials under tension, compression bending, transverse and shear loads. Hardness test on metals can also be conducted.

Principal of Operation :

Operation of the machines is by hydraulic transmission of load from the test specimen to a separately housed load indicator. The hydraulic system is ideal since it replaces transmission of load through levers and knife edges, which are prone to wear and damage due to shock on rupture of test pieces.

The Load is applied by a hydrostatically lubricated ram. Main cylinder pressure is transmitted to the cylinder of the pendulum dynamometer system housed in the control panel. The tansducer gives the signal to the electronic display unit, corresponding to the load exerted by the main ram.simultaneously the digital electronic fitted on the straining unit gives the mechanical displacement to the electronic display unit. Both the signals are processed by the microprocessor and load & displacement is displayed.

Machine consists of :

Straining Unit

This consists of a hydraulic cylinder motor with chain and sprocket drive and a table coupled with the ram of the hydraulic cylinder, mounted on to a robust base. The cylinder and the ram are individually lapped to eliminate friction. The upper cross-head is connected to two screwed columns which are driven by a motor. Axial loading of the ram is ensured be reveling the cylinder and ram of of any possible side loading by the provision of ball seatings.

An elongation scale with a minimum graduation of 1 mm, is provided to measure the deformation of the specimen.

Power Pack :

The power pack generates the maximum pressure of 200 kgf/cm² the hydraulic pump provides continuously non-pulsating oil flow. Hence the load application is very smooth.

Hydraulic Controls :

Hand operated wheels are used to control the flow to and from the hydraulic cylinder. The regulation of oil flow is infinitely variable incorporated in the hydraulic system is a regulating valve which maintains a practically constant rate of piston movement. Control by this valve allows extensometer readings to be taken.

Load Indicator System :

This system consists of a large dial and a pointer. A dummy pointer is provided to register the maximum load reached during the test. Different measuring ranges can be selected by operating the range selection knob. An overload trip switch is incorporated which automatically cuts out the pump motor when the load range in use is exceeded.

Pendulum Dynamometer:

This unit permits selection of favorable hydraulic ratios producing relatively small frictional forces. Pressurized oil in the loading cylinder pushes up the measuring piston proportionately and actuates the special dynamometer system. The piston is constantly rotated to eliminate friction. The dynamometer

system is also provided with an integral damper and ensures high reliability of operation. The load transmitted to the dynamometer is transferred through a pendulum to the load indicator.

Autographic Continuous Roll Load-Elongation Recorder :

This unit is of the pen and drum type and is supplied as standard. The horizontal motion of the pen produces the load ordinate of the diagram and the drum rotation produces the extension ordinates in the ratio of either 1:5 or 1:10.

Accuracy & Calibration :

All VEW Electronic Universal Testing Machines are closely controlled for sensitivity, accuracy and calibration during every stage of manufacture. Every machine is then calibrated over each of its measuring ranges in accordance with the procedure laid down in BS : 1610 : Part 1 :1992 and IS 1828 : (Part 1) : 1991.

VEW Electronic Universal Testing Machines comply with Grade "A" of BS : 1610 : Part 1:1992 and class 1 of IS 1828 : (Part1) : 1991 An accuracy of + 1.0% is guaranteed from 20% from 20% of the load range selected to full load. Below 20% of the selected range, the maximum permissible error is 0.2% of the full load reading.

Special Accessories :

These include load stabilizer, Brinell test Attachment, Bend Test Attachment, Shear Test Attachment and a wide range accessories offered on request at additional cost.

Installation :

It is recommended that machines be erected on a foundation. Details on foundation can be given on request

Specifications :

Maximum Capacity	kN	1500
Measuring Range	kN	0-1500
Load Resolution (20,000 counts full scale)	N	75
Load Range with Accuracy of measurement $\pm 1.0\%$	kN	40 to 1500
Resolution of piston movement (Displacement)	mm	0.1
Clearance for tensile at fully descended working piston.	mm	50-850
Clearance for compression test at fully descended working piston.	mm	0-850
Clearance between columns.	mm	850
Ram Stroke	mm	250

Straining/piston speed (at no load)	mm/min	0-65
Connected Load		
Power	kW	4.9
V		400-440
Ø		3
Dimensions		
L x W x H (approx.)	mm	2750 x 1000 x 3200 x
Weight (approx.)	kg-	6500
Standard Accessories		
For Tension Test		
• Clamping jaws for round specimens of Diameters.	mm	10-25 25-45 45-70
• Clamping jaws for flat specimens of thickness.	mm	0 - 22 22 - 44 44 - 70
Width	mm	90
For Compression Test		
Pair of compression plates of dia.	mm	220
For Transverse Test		
Table with adjustable rollers width of rollers.	mm	160
Diameter of Rollers	mm	50
Maximum clearance between supports	mm	900

Radius of punch tops.

mm

16,22

Accuracy and Calibration :

All VEW Electronic Universal Testing Machines are closely controlled for sensitivity, accuracy and calibration during every stage of manufacture. Every machine is then calibrated over each of its measuring ranges in accordance with the procedure laid down in British standards. 1610 : Part1 : 1992 and IS : 1828 : Part1 : 1991.

FIE Electronic Universal Testing Machine comply with Grade "A" of BS : 1610 : Part1 : 1992 and class 1 of IS-1828-Part-1:1991. An accuracy of $\pm 1\%$ is guaranteed from 2% to 100% of the capacity of the machine.

Below 20% of the selected range, the maximum permissible error is 0.2% of the full load reading.

Specification :

Special Accessories :

- Load Stabilizer
- Printer
- Plotter
- Brinell Test Attachment
- Electronic Extensometer
- Piston Movement Resolution of 0.01 mm
- Electronic Load Pacer
- Shear Test Attachment
- Software Packages
- Mechanical Extensometer

- Wide range accessories offered on request at additional cost.
 - Due to constant R& D specifications & features are subject to change without notice.
 - The dimensions given above are approximate.
-